

MAE 146 HW#5. Design project part 1 calculations.

Nasser Abbasi

May 23, 2003

Contents

| | |
|--|----|
| 1 Problem | 2 |
| 2 Assumptions | 2 |
| 3 Method | 2 |
| 4 Analysis | 3 |
| 4.1 Common calculations | 3 |
| 4.2 Decide how to correct the LEO plane inclination | 4 |
| 4.2.1 First scenario. All plane correction at perigee. | 4 |
| 4.2.2 Second scenario. All plane correction at apogee. | 6 |
| 4.2.3 Third Scenario. Partial plane correction at perigee. Rest at apogee. | 7 |
| 4.2.4 Summary of scenarios to correct plane inclination | 9 |
| 4.3 Calculate time to move from LEO to GEO | 10 |
| 4.4 Decide when to inject to GEO. Calculate lead angle β and rendezvous with first satellite | 10 |
| 4.4.1 First option. Inject to GEO at $t = 0$ | 11 |
| 4.4.2 second option: phase-wait in the LEO orbit until the correct lead angle β reached at one end of lines of nodes. | 14 |
| 4.4.3 Third option: phase-wait in the LEO orbit until the correct lead angle β reached at the other end of lines of nodes. | 18 |
| 4.4.4 Fourth option. phase-wait in the LEO orbit until smallest difference to β reached first time. | 19 |
| 4.4.5 Summary of lead angle β scenarios | 22 |
| 4.5 Rendezvous with the second satellite | 22 |
| 4.6 Stay locked in with the second satellite. | 23 |
| 4.7 reposition to final destination. | 23 |
| 5 Summary and Results | 24 |
| 6 Appendix | 26 |