

HW 9

Math 501 Numerical analysis

Spring, 2007
California State University, Fullerton

Nasser M. Abbasi

August 13, 2021 Compiled on August 13, 2021 at 10:04pm

Contents

1	Source code	8
1.1	nma_inverse_power.m	8
1.2	nma_inverse_shifted_power.m	8
1.3	nma_power.m	9
1.4	nma_shifted_power.m	10
1.5	nma_test.m	10

W/W

HW # 9

Math 501

Nasser Abbasi

April 11, 2007.

Problem # 9, Section 4.7

Computer Assignment 4/4/2007

Iterative Eigen Values

Power

Inverse Power

Shifted Power

Shifted Inverse Power

problem # 9, section 4.7

let A be $n \times n$, and A -orthonormal system exist, show that A is SPD.

Solution outline express \bar{x} in terms of basis (\bar{u}^i) , start with definition of $\bar{x}^T A \bar{x}$, show this must be > 0 utilize property of A -orthonormal to cancel terms:

Solution given A $n \times n$

given A -orthonormal system $[\bar{u}^1 | \bar{u}^2 | \dots | \bar{u}^n]$

$$\text{i.e. } \langle \bar{u}^i, A \bar{u}^j \rangle = \delta_{ij}$$

$$(1) \quad \left\{ \begin{array}{lll} \text{i.e.} & (\bar{u}^1)^T A \bar{u}^1 = 1 & (\bar{u}^2)^T A \bar{u}^1 = 0 \quad \dots \quad (\bar{u}^n)^T A \bar{u}^1 = 0 \\ & (\bar{u}^1)^T A \bar{u}^2 = 0 & (\bar{u}^2)^T A \bar{u}^2 = 1 \quad (\bar{u}^n)^T A \bar{u}^2 = 0 \\ & (\bar{u}^1)^T A \bar{u}^3 = 0 & \vdots \quad \vdots \quad \vdots \\ & \vdots & \vdots \\ & (\bar{u}^1)^T A \bar{u}^n = 0 & (\bar{u}^2)^T A \bar{u}^n = 0 \dots (\bar{u}^n)^T A \bar{u}^n = 1 \end{array} \right.$$

now A is SPD if $\bar{x}^T A \bar{x} > 0$ ($\bar{x} \neq 0$)

since \bar{u}^i are Basis in \mathbb{R}^n , we can write vector \bar{x} in terms of these basis. so

$$\bar{x} = \langle \bar{x}, \bar{u}^1 \rangle \bar{u}^1 + \langle \bar{x}, \bar{u}^2 \rangle \bar{u}^2 + \dots + \langle \bar{x}, \bar{u}^n \rangle \bar{u}^n$$

hence using this, we now write $\bar{x}^T A \bar{x}$ and compare to (1)

$$\bar{x}^T A \bar{x} = (\langle \bar{x}, \bar{u}^1 \rangle \bar{u}^1 + \langle \bar{x}, \bar{u}^2 \rangle \bar{u}^2 + \dots + \langle \bar{x}, \bar{u}^n \rangle \bar{u}^n)^T A (\langle \bar{x}, \bar{u}^1 \rangle \bar{u}^1 + \dots + \langle \bar{x}, \bar{u}^n \rangle \bar{u}^n)$$

let $\langle \bar{x}, \bar{u}^1 \rangle = a_1$, $\langle \bar{x}, \bar{u}^2 \rangle = a_2$ etc... these are the coordinates of \bar{x} in this subspace. so we write

$$\bar{x}^T A \bar{x} = (a_1 \bar{u}^1 + a_2 \bar{u}^2 + \dots + a_n \bar{u}^n)^T A (a_1 \bar{u}^1 + a_2 \bar{u}^2 + \dots + a_n \bar{u}^n)$$

$$= (a_1 \bar{u}^1 + a_2 \bar{u}^2 + \dots + a_n \bar{u}^n)^T (A a_1 \bar{u}^1 + A a_2 \bar{u}^2 + \dots + A a_n \bar{u}^n)$$

$$= a_1^2 (\bar{u}^1)^T A \bar{u}^1 + a_1 a_2 (\bar{u}^1)^T A \bar{u}^2 + a_1 a_3 (\bar{u}^1)^T A \bar{u}^3 + \dots + a_1 a_n (\bar{u}^1)^T A \bar{u}^n$$

$$+ a_2 a_1 (\bar{u}^2)^T A \bar{u}^1 + a_2^2 (\bar{u}^2)^T A \bar{u}^2 + a_2 a_3 (\bar{u}^2)^T A \bar{u}^3 + \dots + a_2 a_n (\bar{u}^2)^T A \bar{u}^n$$

$$\dots + a_n a_1 (\bar{u}^n)^T A \bar{u}^1 + a_n a_2 (\bar{u}^n)^T A \bar{u}^2 + \dots + a_n^2 (\bar{u}^n)^T A \bar{u}^n$$

So we see the pattern for $\bar{x}^T A \bar{x}$ as

$$\begin{aligned}
 &= a_1^2 (\bar{u}^1)^T A \bar{u}^1 + \dots + \dots + \dots \quad (2) \\
 &\quad + a_2^2 (\bar{u}^2)^T A \bar{u}^2 + \dots \\
 &\quad \dots \dots \dots \dots \dots \dots \\
 &\quad + a_n^2 (\bar{u}^n)^T A \bar{u}^n + \dots
 \end{aligned}$$

But since from (1) we see that $(\bar{u}^1)^T A \bar{u}^1 = 1$,
 $(\bar{u}^2)^T A \bar{u}^2 = 1, \dots, (\bar{u}^n)^T A \bar{u}^n = 1$ and
everything else is Zero, then (2) can
be written as

$$\bar{x}^T A \bar{x} = a_1^2 + a_2^2 + a_3^2 + \dots + a_n^2$$

but the a_i are the coordinates of \bar{x} in \mathbb{R}^n .

and for $\bar{x} \neq \bar{0}$, then at least one coordinate
must not vanish. Hence $\bar{x}^T A \bar{x} \neq 0$.

In addition, since the coordinates are all squared

hence it is positive sum.

$$\implies \boxed{\bar{x}^T A \bar{x} > 0} \text{ ie } A \text{ is SPD} \quad \text{QED}$$

Name: Nasser Abbasi
 Math 501 – Numerical Analysis & Computation – Dr. Lee - Spring 2007

Computer Assignment 04/04/2007

- 1) Implement in MATLAB the following iterative Eigen methods:
 - a) Power
 - b) Inverse Power
 - c) Shifted Power
 - d) Shifted Inverse Power

- 2) Suppose $A = \begin{bmatrix} 4 & 2 & 1 & 0 & 0 \\ 1 & 4 & 1 & 1 & 0 \\ 2 & 1 & 4 & 1 & 2 \\ 0 & 1 & 1 & 4 & 1 \\ 0 & 0 & 1 & 2 & 4 \end{bmatrix}$ and start with $\vec{w}^{(0)} = \begin{bmatrix} 1 \\ 1 \\ 1 \\ 1 \\ 1 \end{bmatrix}$, find with 10 iterations:
 - a) The dominant eigenpair of A
 - b) The least dominant eigenpair of A
 - + c) The eigenpair of A farthest to 2
 - d) The eigenpair of A closest to 6.5

```

%
% MATH 501, Computer Assignment 04/04/2007
% by Nasser Abbasi
%
% test script to run problem 2 on the data given
%
A=[4 2 1 0 0;
   1 4 1 1 0;
   2 1 4 1 2;
   0 1 1 4 1;
   0 0 1 2 4];
initialEigenVectorGuess=[1 1 1 1 1];

%use Matlab to see the values to verify against
[v,l]=eig(A)

%Set parameters
maxIter=10;
delErr=0.0001; %not specified, try these
delEps=0.0001; %not specified, try these

[lambda]=nma_power(A,initialEigenVectorGuess,maxIter,delErr,delEps);
fprintf('----- power result. Eigenvalue=%f\n',lambda);

[lambda]=nma_inverse_power(A,initialEigenVectorGuess,maxIter,delErr,delEps);
fprintf('----- power inverse result. Eigenvalue=%f\n',lambda);

[lambda,k]=nma_shifted_power(A,initialEigenVectorGuess,maxIter,delErr,delEps,2);
lambda=2+lambda;
fprintf('----- power shifted result. Eigenvalue=%f\n',lambda);

[lambda,k]=nma_inverse_shifted_power(A,initialEigenVectorGuess,maxIter,delErr,delEps,6.5);
lambda=6.5+lambda;
fprintf('----- power inverse shifted result. Eigenvalue=%f\n',lambda);

TEST RESULT
v =

```

-0.3861	-0.6325	0.0000	0.2405	-0.5000
-0.3861	-0.3162	0.4082	0.2405	0.5000
-0.6354	0.0000	-0.8165	-0.8767	-0.0000
-0.3861	0.3162	0.4082	0.2405	-0.5000
-0.3861	0.6325	0.0000	0.2405	0.5000

```

l =

```

7.6458	0	0	0	0
0	5.0000	0	0	0
0	0	3.0000	0	0
0	0	0	2.3542	0
0	0	0	0	2.0000

```

----- power result. Eigenvalue=7.645769
----- power inverse result. Eigenvalue=2.354139
----- power shifted result. Eigenvalue=7.645755
----- power inverse shifted result. Eigenvalue=7.645724

```

```

function
[lambda_new,k]=nma_inverse_shifted_power(A,initialEigenVectorGuess,maxIter,delE
rr,delEps,mu)
%
% MATH 501, Computer Assignment 04/04/2007
% by Nasser Abbasi
%
% IMPLEMENT iterative Inverse shifted power method

w_old=initialEigenVectorGuess(:);
lambda_old=rand;
In=eye(size(A,1));
A=inv(A-mu*In);

for k=1:maxIter
    w_old=w_old/norm(w_old);
    w_new=A*w_old;
    lambda_new=dot(w_old,w_new);

    if norm(w_new-w_old)<delErr || abs(lambda_old-lambda_new)<delEps
        break;
    else
        w_old=w_new;
        lambda_old=lambda_new;
    end
end
lambda_new=1/lambda_new;

=====
function [lambda_new,k]=nma_shifted_power(A,initialEigenVectorGuess, ...
maxIter,delErr,delEps,mu)
%
% MATH 501, Computer Assignment 04/04/2007
% by Nasser Abbasi
%
% IMPLEMENT iterative shifted power method

w_old=initialEigenVectorGuess(:);
lambda_old=mu;
In=eye(size(A,1));
A=A-mu*In;

for k=1:maxIter
    w_old=w_old/norm(w_old);
    w_new=A*w_old;
    lambda_new=dot(w_old,w_new);

    if norm(w_new-w_old)<delErr || abs(lambda_old-lambda_new)<delEps
        break;
    else
        w_old=w_new;
        lambda_old=lambda_new;
    end
end

```

1 Source code

1.1 nma_inverse_power.m

```
nction lambda_new=nma_inverse_power(A,initialEigenVectorGuess,maxIter,delErr,delEps)
%
% MATH 501, Computer Assignment 04/04/2007
% by Nasser Abbasi
%
% IMPLEMENT iterative Inverse power method

A=inv(A);

w_old=initialEigenVectorGuess(:);
lambda_old=rand;

for k=1:maxIter
    w_old=w_old/norm(w_old);
    w_new=A*w_old;
    lambda_new=dot(w_old,w_new);

    if norm(w_new-w_old)<delErr || abs(lambda_old-lambda_new)<delEps
        break;
    else
        w_old=w_new;
        lambda_old=lambda_new;
    end
end

lambda_new=1/lambda_new;
```

1.2 nma_inverse_shifted_power.m

```
function [lambda_new,k]=nma_inverse_shifted_power(A,initialEigenVectorGuess,maxIter,delErr,de
%
% MATH 501, Computer Assignment 04/04/2007
% by Nasser Abbasi
%
% IMPLEMENT iterative Inverse shifted power method

w_old=initialEigenVectorGuess(:);
lambda_old=rand;
In=eye(size(A,1));
A=inv(A-mu*In);

for k=1:maxIter
    w_old=w_old/norm(w_old);
```

```
w_new=A*w_old;
lambda_new=dot(w_old,w_new);

if norm(w_new-w_old)<delErr || abs(lambda_old-lambda_new)<delEps
    break;
else
    w_old=w_new;
    lambda_old=lambda_new;
end
end

lambda_new=1/lambda_new;
```

1.3 nma_power.m

```
function lambda_new=nma_power(A,initialEigenVectorGuess,maxIter,delErr,delEps)
%
% MATH 501, Computer Assignment 04/04/2007
% by Nasser Abbasi
%
% IMPLEMENT iterative power method

w_old=initialEigenVectorGuess(:);

lambda_old=rand;

for k=1:maxIter
    w_old=w_old/norm(w_old);
    w_new=A*w_old;
    lambda_new=dot(w_old,w_new);
    if norm(w_new-w_old)<delErr || abs(lambda_old-lambda_new)<delEps
        break;
    else
        w_old=w_new;
        lambda_old=lambda_new;
    end
end
```

1.4 nma_shifted_power.m

```

nction [lambda_new,k]=nma_shifted_power(A,initialEigenVectorGuess, ...
    maxIter,delErr,delEps,mu)
%
% MATH 501, Computer Assignment 04/04/2007
% by Nasser Abbasi
%
% IMPLEMENT iterative shifted power method

w_old=initialEigenVectorGuess(:);
lambda_old=mu;
In=eye(size(A,1));
A=A-mu*In;

for k=1:maxIter
    w_old=w_old/norm(w_old);
    w_new=A*w_old;
    lambda_new=dot(w_old,w_new);

    if norm(w_new-w_old)<delErr || abs(lambda_old-lambda_new)<delEps
        break;
    else
        w_old=w_new;
        lambda_old=lambda_new;
    end
end

```

1.5 nma_test.m

```

%
% MATH 501, Computer Assignment 04/04/2007
% by Nasser Abbasi
%
% test script to run problem 2 on the data given

A=[4 2 1 0 0;
   1 4 1 1 0;
   2 1 4 1 2;
   0 1 1 4 1;
   0 0 1 2 4];
initialEigenVectorGuess=[1 1 1 1 1];

%use Matlab to see the values to verify against

[v,l]=eig(A)

```

```
%Set parameters
maxIter=10;
delErr=0.0001; %not specified, try these
delEps=0.0001; %not specified, try these

[lambda]=nma_power(A,initialEigenVectorGuess,maxIter,delErr,delEps);
fprintf('----- power result. Eigenvalue=%f\n',lambda);

[lambda]=nma_inverse_power(A,initialEigenVectorGuess,maxIter,delErr,delEps);
fprintf('----- power inverse result. Eigenvalue=%f\n',lambda);

[lambda,k]=nma_shifted_power(A,initialEigenVectorGuess,maxIter,delErr,delEps,2);
lambda=2+lambda;
fprintf('----- power shifted result. Eigenvalue=%f\n',lambda);

[lambda,k]=nma_inverse_shifted_power(A,initialEigenVectorGuess,maxIter,delErr,delEps,6.5);
lambda=6.5+lambda;
fprintf('----- power inverse shifted result. Eigenvalue=%f\n',lambda);
```